

## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** Window & Door Silicone 312 Ral 7038

**Other means of identification:**

Not relevant

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses (Consumer use): Sealant

Relevant uses (Professional users): Sealant

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

WOLF GROUP IBERICO S.A.U  
 AVDA. BERTRAN GÜELL, 78  
 08850 GAVÀ - BARCELONA - SPAIN  
 Phone: +34 936629911  
 QHSE.es@wolf-group.com  
 www.wolf-group.com

**1.4 Emergency telephone number:** 112

## SECTION 2: HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture:**

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

**2.2 Label elements:**

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):****Warning****Hazard statements:**

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing vapours

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of the contents and/or its container using the separate collection system in your municipality.

**Supplementary information:**

Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine.

**Substances that contribute to the classification**

Butan-2-one O,O',O''-(vinylsilylidyne)trioxime

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 Substance:**

Not relevant

- CONTINUED ON NEXT PAGE -

Safety data sheet  
According to UK REACH (S.I. 2019/758)

**Window & Door Silicone 312 Ral 7038**






**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

**3.2 Mixture:**

**Chemical description:** Mixture of polymers, dispersants and organic compounds

**Components:**

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 64742-55-8 EC: 265-158-7 REACH: 01-2119487077-29-XXXX	<b>Distillates (petroleum), hydrotreated light paraffinic, &lt; 3 % IP 346</b> Asp. Tox. 1: H304 - Danger	 5 - <10 %
CAS: Not relevant EC: 917-488-4 REACH: 01-2119458943-27-XXXX	<b>Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b> Asp. Tox. 1: H304; EUH066 - Danger	 2,5 - <5 %
CAS: 2224-33-1 EC: 218-747-8 REACH: 01-2119970537-27-XXXX	<b>Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime</b> Eye Dam. 1: H318; Skin Sens. 1B: H317; STOT RE 2: H373 - Danger	 2,5 - <5 %
CAS: 58190-57-1 EC: 611-631-1 REACH: 01-2119982962-22-XXXX	<b>2-Propanone, 2,2',2''-[O,O',O''-(ethylsilyldiyl)trioxime]</b> STOT RE 2: H373 - Warning	 1 - <2,5 %
CAS: 1760-24-3 EC: 217-164-6 REACH: 01-2119970215-39-XXXX	<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine</b> Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	 0,1 - <1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

- CONTINUED ON NEXT PAGE -

## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 5: FIREFIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

Non-applicable

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

**6.4 Reference to other sections:**

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

- CONTINUED ON NEXT PAGE -

**Window & Door Silicone 312 Ral 7038**

**SECTION 7: HANDLING AND STORAGE (continued)**

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	5.58 mg/m <sup>3</sup>
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.15 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	1.06 mg/m <sup>3</sup>	Not relevant
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1 EC: 611-631-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.059 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.419 mg/m <sup>3</sup>	Not relevant

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	1.19 mg/m <sup>3</sup>
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	Oral	Not relevant	Not relevant	0.075 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0.075 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.26 mg/m <sup>3</sup>	Not relevant
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1 EC: 611-631-1	Oral	Not relevant	Not relevant	0.03 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0.03 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0.103 mg/m <sup>3</sup>	Not relevant

**PNEC:**

Identification				
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	STP	Not relevant	Fresh water	Not relevant
	Soil	Not relevant	Marine water	Not relevant
	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	9.33 g/kg	Sediment (Marine water)	Not relevant

- CONTINUED ON NEXT PAGE -

**Window & Door Silicone 312 Ral 7038**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**


Identification				
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	STP	4.06 mg/L	Fresh water	0.019 mg/L
	Soil	133.8 mg/kg	Marine water	0.002 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	1136.562 mg/kg
	Oral	0.003333 g/kg	Sediment (Marine water)	113.656 mg/kg
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1 EC: 611-631-1	STP	2.398 mg/L	Fresh water	0.24 mg/L
	Soil	240.95 mg/kg	Marine water	0.024 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	2047.053 mg/kg
	Oral	0.002638 g/kg	Sediment (Marine water)	204.705 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	STP	25 mg/L	Fresh water	0.062 mg/L
	Soil	0.009 mg/kg	Marine water	0.006 mg/L
	Intermittent	0.62 mg/L	Sediment (Fresh water)	0.22 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.022 mg/kg

**8.2 Exposure controls:**


**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Remarks
 Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019

**F.- Additional emergency measures**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

**The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:**

V.O.C. (Supply):	0.03 % weight
V.O.C. density at 20 °C:	0.41 kg/m <sup>3</sup> (0.41 g/L)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Paste
Colour:	 Grey
Odour:	Not relevant *
Odour threshold:	Not relevant *

**Volatility:**

Boiling point at atmospheric pressure:	200 °C
Vapour pressure at 20 °C:	29 Pa
Vapour pressure at 50 °C:	129.93 Pa (0.13 kPa)
Evaporation rate at 20 °C:	Not relevant *

**Product description:**

Density at 20 °C:	1447.2 kg/m <sup>3</sup>
Relative density at 20 °C:	1.447
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>20.5 mm <sup>2</sup> /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

**Flammability:**

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	260 °C

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Lower flammability limit: Not relevant \*

Upper flammability limit: Not relevant \*

**Particle characteristics:**

Median equivalent diameter: Not relevant \*

**9.2 Other information:****Information with regard to physical hazard classes:**

Explosive properties: Not relevant \*

Oxidising properties: Not relevant \*

Corrosive to metals: Not relevant \*

Heat of combustion: Not relevant \*

Aerosols-total percentage (by mass) of flammable components: Not relevant \*

**Other safety characteristics:**

Surface tension at 20 °C: Not relevant \*

Refraction index: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -

**Window & Door Silicone 312 Ral 7038**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Causes serious eye irritation.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Toluene (3); Carbon black (2B); Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:
 

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:
 

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylydyne)trioxime] CAS: 58190-57-1 EC: 611-631-1	LD50 oral	2500 mg/kg	Rat
	LD50 dermal	2493 mg/kg	Rat
	LC50 inhalation vapour	>20 mg/L	
Butan-2-one O,O',O''-(vinylsilylydyne)trioxime CAS: 2224-33-1 EC: 218-747-8	LD50 oral	3519 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation mist	>5.53 mg/L (4 h)	Rat
Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS: Not relevant EC: 917-488-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	

- CONTINUED ON NEXT PAGE -

## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	2295 mg/kg	>2000 mg/kg	Rat
	>2000 mg/kg	>20 mg/L	
	>20 mg/L		

## Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Oral	>2000 mg/kg (Calculation method)	0 %	
Dermal	>2000 mg/kg (Calculation method)	0 %	
LC50 inhalation vapour	>20 mg/L (4 h) (Calculation method)	0 %	

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

## 12.1 Toxicity:

## Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8	5000 mg/L (96 h)	1000 mg/L (48 h)	Oncorhynchus mykiss	Fish
	1000 mg/L (96 h)	1000 mg/L (96 h)	Daphnia magna	Crustacean
	1000 mg/L (96 h)	1000 mg/L (96 h)	Scenedesmus subspicatus	Algae
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1	55000 mg/L (96 h)	17168 mg/L (48 h)	QSAR	Fish
	17168 mg/L (48 h)	1429 mg/L (96 h)	QSAR	Fish
	1429 mg/L (96 h)	1429 mg/L (96 h)	QSAR	Fish
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1	697 mg/L (96 h)	679 mg/L (48 h)	Pimephales promelas	Fish
	679 mg/L (48 h)	315 mg/L (72 h)	N/A	Crustacean
	315 mg/L (72 h)	315 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	597 mg/L (96 h)	81 mg/L (48 h)	Brachydanio rerio	Fish
	81 mg/L (48 h)	8.8 mg/L (72 h)	Daphnia magna	Crustacean
	8.8 mg/L (72 h)	8.8 mg/L (72 h)	Selenastrum capricornutum	Algae

## Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC	NOEC		
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1	50 mg/L	100 mg/L	Oryzias latipes	Fish
	100 mg/L	100 mg/L	Daphnia magna	Crustacean

## 12.2 Persistence and degradability:

## Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	Not relevant	Not relevant	20 mg/L	28 days
	Not relevant	Not relevant	% Biodegradable	0 %
	Not relevant	Not relevant	% Biodegradable	39 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	Not relevant	Not relevant	Not relevant	28 days
	Not relevant	Not relevant	Not relevant	28 days
	Not relevant	Not relevant	% Biodegradable	39 %

## 12.3 Bioaccumulative potential:

## Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	Pow Log
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	3.9	
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime CAS: 2224-33-1 EC: 218-747-8	1	0.6
	Low	

- CONTINUED ON NEXT PAGE -

**Window & Door Silicone 312 Ral 7038**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Bioaccumulation potential	
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1 EC: 611-631-1	BCF	
	Pow Log	9.83
	Potential	

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidyne)trioxime] CAS: 58190-57-1	Koc	85500	Henry	Not relevant
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	Non-hazardous

**Type of waste:**

Not relevant

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

**SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport (ADR/RID,IMDG,IATA)

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

**The Control of Major Accident Hazards Regulations 2015:**

Not relevant

**Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

## Safety data sheet

According to UK REACH (S.I. 2019/758)

## Window &amp; Door Silicone 312 Ral 7038

## SECTION 15: REGULATORY INFORMATION (continued)

**Other legislation:**

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.  
 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.  
 Control of Substances Hazardous to Health Regulations 2002 (as amended)  
 EH40/2005 Workplace exposure limits.

## SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

**Texts of the legislative phrases mentioned in section 2:**

H319: Causes serious eye irritation.  
 H317: May cause an allergic skin reaction.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
 Eye Dam. 1: H318 - Causes serious eye damage.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

**Classification procedure:**

Eye Irrit. 2: Calculation method  
 Skin Sens. 1B: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
 IMDG: International maritime dangerous goods code  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organisation  
 COD: Chemical Oxygen Demand  
 BOD5: 5day biochemical oxygen demand  
 BCF: Bioconcentration factor  
 LD50: Lethal Dose 50  
 LC50: Lethal Concentration 50  
 EC50: Effective concentration 50  
 LogPOW: Octanolwater partition coefficient  
 Koc: Partition coefficient of organic carbon  
 UFI: unique formula identifier  
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -