

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-023100

Version 24.01.2024



1 / 2

1. Unique identification code of the product-type:

Penosil FireStop Silicone 331 300ml

2. Intended use/uses:

Sealant for facade for interior and exterior applications, suitable for use in cold climates (F-EXT-INT-CC)

3. Manufacturer:

Wolf Group OÜ
Suur-Paala 10
13619 Tallinn
ESTONIA

4. Authorized representative:

Not relevant

5. System or systems of assessment and verification of constancy of performance (AVCP):

System 3 for the type testing
System 3 for the reaction to fire

6. Harmonised standard:

EN 15651-1:2012

Notified body/ies:

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION
0074 - GINGER CEBTP

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-023100

Version 24.01.2024



2 / 2

7.1 Declared performance:

EN 15651-1:2012; Type F-EXT-INT-CC, class 25HM

Essential characteristics:	Performance:	Harmonised technical specification
Reaction to fire	Class B	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD/see product safety data sheet	
Water tightness and air tightness, as:		
• Resistance to flow (EN ISO 7390)	≤3 mm	
• Loss of volume (EN ISO 10563)	≤10 %	
• Tensile properties at maintained extension at -30°C (EN ISO 8340)	NF	
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF	
Durability:	Pass	
Conditioning method A / Tested on concrete M2, anodized aluminium, without primer		

NPD = No performance determined.
 NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo
 Product Manager
 13619 Tallinn, Estonia
 24.01.2024



1292 / 0074

Wolf Group OÜ
Suur-Paala 10
13619 Tallinn
ESTONIA
22
DoP Nr: KR-023100

EN 15651-1:2012

Sealant for facade for interior and exterior applications, suitable for use in cold climates

Type: F-EXT-INT-CC

Conditioning: method A

Substrate: concrete M2, anodized aluminium, without primer

Reaction to fire	Class B
Release of chemicals dangerous to the environment and health	NPD/see product safety data sheet
Water tightness and air tightness, as:	
• Resistance to flow (EN ISO 7390)	≤3 mm
• Loss of volume (EN ISO 10563)	≤10 %
• Tensile properties at maintained extension at -30°C (EN ISO 8340)	NF
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF
Durability:	Pass