

TECHNICAL DATA SHEET

PENOSIL Spray Silicone 353

A silicone based lubricant spray for reducing friction and waterproofing metal parts, polishing plastics, demoulding rubber, etc.

Main benefits

- Waterproof
- Sprayable
- Reduces friction
- Non-stick coating
- Polishes plastics and rubbers
- Protects metal parts

Fields of application

- Multipurpose non-stick lubricant spray.
- Demoulding all types of plastics and rubber.
- Increases the conservation of moulds, keeping them clean, with minimal wear and achieving a better appearance of the pieces.
- Polishing plastics and waterproofing awnings, canvas, footwear, etc.
- Lubricating locks, ramps, guides, conveyor belts, blades, saws, etc.
- Protecting metal parts against humidity and dust, as well as against corrosion in anodized aluminium parts.
- Protecting welding works.

Application instructions

Application conditions

Air temperature during use: +10 °C to +35 °C.

Surface preparation

Surfaces must be dry and clean from dust and loose particles. Shake the can slightly before use.

Application method

Apply a thin and uniform layer of silicone from approx. 30 cm distance. The silicone layer's thickness can be adjusted with distance.

Cleaning

Wipe off any excess silicone using a cloth or cleaning wipe.

Colour

Transparent.

Package

400 ml aerosol can, 12 pcs in a box.

Storage conditions and shelf life

Guaranteed shelf life is 12 months from production date if stored in an unopened packaging in a cool and dry place at +5 °C to +30 °C. Do not expose to temperature over +50°C, do not keep near heat sources or in direct sunlight. Store and transport in upright position. Secure cans before transport.

Limitations

- Please observe the expiration date!

Safety regulations

Pressurized canister. Use only in well-ventilated areas. When using indoors, ventilate the room after application of foam. Do not smoke during application! Use protective gear when necessary. Keep out of the reach of children.

See label and safety data sheet (SDS) for more information.

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice. This TDS replaces and supersedes all previous data sheets on the same product.