

Declaration of Performance

In accordance with Annex III of Regulation (EU) No 305/2011
amended by Commission Delegated Regulation (EU) No 574/2014



PENOSIL Building Silicone 376

DoP Nr.: PE-1223609

- **Unique identification code of the product-type:**

PENOSIL Building Silicone 376

- **Intended use/uses:**

Non-structural elastic sealant intended for sealing facade elements in building construction, including the interior face (intended for use in cold climates: -30°C):

EN 15651-1; **type F-EXT-INT-CC**

Non-structural elastic sealant used for sealing glazing in building construction (intended for use in cold climates: -30°C):

EN 15651-2; **type G-CC**

- **Manufacturer:**

WOLF GROUP IBÉRICO S.A.U.
Av. Bertrán Güell, 78.
E-08850 GAVÁ (Barcelona)
SPAIN

- **System or systems of assessment and verification of constancy of performances (AVCP):**

System 3 for the type testing.

System 3 for the reaction to fire.

- **Harmonised standard:**

EN 15651-1 :2012 / EN 15651-2 :2012

Notified body/ies:

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

Declaration of Performance

In accordance with Annex III of Regulation (EU) No 305/2011
amended by Commission Delegated Regulation (EU) No 574/2014



PENOSIL Building Silicone 376

DoP Nr.: PE-1223609

Declared performances:

<u>Essential characteristics</u>	<u>Declared Performance</u>	<u>Harmonised technical specification</u>
Reaction to fire: (EN 13501-1:2007 + A1:2010)	Class E	EN 15651-1 :2012
Release of chemicals dangerous to the environment and health:	See product safety data sheet	
Water tightness and air tightness as determined by:		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 40 %	
• Tensile properties at maintained extension at -30°C (modif. EN ISO 8340)	NF	
• Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	
Durability:	Pass	

Conditioning: Method A (according to ISO 8340) / NF = No failure according to EN ISO 11600

Substrates: Glass and mortar-M2, without primer.

<u>Essential characteristics</u>	<u>Declared Performance</u>	<u>Harmonised technical specification</u>
Reaction to fire: (EN 13501-1:2007 + A1:2010)	Class E	EN 15651-2 :2012
Release of chemicals dangerous to the environment and health:	See product safety data sheet	
Water tightness and air tightness as determined by:		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 40 %	
• Tensile properties at maintained extension at -30°C (modif. EN ISO 8340)	NF	
• Elastic recovery (EN ISO 7389)	≥ 60 % at 60% elongation	
• Adhesion/cohesion properties after exposure to heat, water, and artificial light (EN ISO 11431)	NF at 60% elongation	
Durability:	Pass	

Conditioning: Method A (according to ISO 8340) / NF = No failure according to EN ISO 11600

Substrates: Glas and mortar-M2, without primer.

Declaration of Performance

In accordance with Annex III of Regulation (EU) No 305/2011
amended by Commission Delegated Regulation (EU) No 574/2014



PENOSIL Building Silicone 376

DoP Nr.: PE-1223609

- **Declaration:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Gavà, Barcelona (España)
08 / 05 / 2023

José M. Martínez
R&D Manager
WOLF GROUP IBÉRICO S.A.U.

Disclaimer: The information contained in this DoP is provided in good faith and deemed accurate at the date of publication of this document. Despite the intended uses specified in this document and due to the different conditions of use, the user is obliged to ensure the product is suitable for its particular application and is legally compliant for it. This information should not be construed as legal advice. Wolf Group Ibérico S.A.U. makes no warranty express or implied regarding the fitness of the Product for any particular purpose. It is over understood that we warranty the irreproachable quality of our products in accordance with our General Conditions of Sales and Supply.

CE MARKING

PENOSIL Building Silicone 376

 1292	
WOLF GROUP IBÉRICO S.A.U., Av. Bertrán Güell, 78, 08850 Gavà (Barcelona), Spain. 23 PE-1223609	
EN 15651-1 : F-EXT-INT-CC EN 15651-2 : G-CC PENOSIL Building Silicone 376 Sealant for facade elements (exterior and interior), and for glazing, also for use in cold climates.	
Conditioning: Method A Substrates: Glass and mortar-M2, without primer.	
REACTION TO FIRE: RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH: WATER TIGHTNESS AND AIR TIGHTNESS AS DETERMINED BY: - Resistance to flow: - Loss of volume: - Tensile properties, at maintained extension, at -30°C: - Tensile properties at maintained extension after water immersion: - Elastic recovery: - Adhesion/cohesion properties after exposure to heat, water, and artificial light: DURABILITY:	Class E See product safety data sheet ≤ 3 mm ≤ 40% NF NF ≥ 60 % at 60% elongation NF elongation 60% Pass

NF = No failure