

www.penosil.com

Wolf Group Head Office Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

# TECHNICAL DATA SHEET

# **PENOSIL Sealant Finisher 407**

Sealant Finisher is a sealant smoothing spray for flawless sealant finishing bead. Perfect for silicone, acrylic, polyurethane and MS polymer sealant joints. Helps to accelerate sealants skin formation.

#### Main benefits

- Fast
- Low odour
- Sprayable

# Fields of application

 Product designed to smooth joints of all types of sealants. Particularly suitable for sanitary, carpentry, glazing, cold room, and general construction joints. Does not stain the substrates.

# **Application instructions**

#### **Application conditions**

Application temperature: +1 °C to +40 °C.

Colourless viscous liquid.

Density slightly above 1; neutral pH.

Solubility: dispersible in water.

### Application method

Spray the ready-to-use product on the freshly laid sealant joint and smooth it quickly with a spatula in one go.

## Colour

Colourless.

#### **Package**

1000 ml bottle, 5 pcs in a box.

## Storage conditions and shelf life

Guaranteed shelf life 12 months from the manufacturing date when stored in closed original package in a dry place and protected from direct sunlight and heat sources at temperatures between +5 °C and +30 °C.

## **Limitations**

Avoid storage extreme temperatures > +50 °C (product liquefaction). Avoid freezing

#### Safety regulations

Keep out of reach from children. See label and safety data sheet (SDS) for more information.



www.penosil.com

Wolf Group Head Office Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice.

This TDS replaces and supersedes all previous data sheets on the same product.