

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-043100**

Version



1 / 3

---

**1. Unique identification code of the product-type:**

Penosil SilAcryl Elastic 610 300ml

---

**2. Intended use/uses:**

Sealant for facade for interior and exterior applications, suitable for use in cold climates (F-EXT-INT-CC)  
Sealants for joints for non-structural use in sanitary areas (S)

---

**3. Manufacturer:**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**4. Authorized representative:**

Not relevant

---

**5. System or systems of assessment and verification of constancy of performance (AVCP):**

System 3 for the type testing  
System 4 for the reaction to fire

---

**6. Harmonised standard:**

EN 15651-1:2012  
EN 15651-3:2012

**Notified body/ies:**

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-043100**

Version



2 / 3

**7.1 Declared performance:**

EN 15651-1:2012; Type F-EXT-INT-CC Class 12,5E

Essential characteristics:	Performance:	Harmonised technical specification
<b>Reaction to fire</b>	Class F	EN 15651-1:2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD/see product safety data sheet	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow (EN ISO 7390)	≤3 mm	
• Loss of volume (EN ISO 10563)	≤25 %	
• Tensile properties at maintained extension at -30°C (EN ISO 8340)	NF	
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF	
• Adhesion/cohesion at variable temperatures (EN ISO 9047)	NF	
<b>Durability:</b>	Pass	
Conditioning method B / Tested on concrete M2, without primer		

NPD = No performance determined.

NF= No Failure.

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-043100**

Version



3 / 3

**7.2 Declared performance:**

EN 15651-3:2012; Type S Class XS2

Essential characteristics:	Performance:	Harmonised technical specification
<b>Reaction to fire</b>	Class F	EN 15651-3:2012
<b>Release of chemicals dangerous to the environment and health</b>	NPD/see product safety data sheet	
<b>Water tightness and air tightness, as:</b>		
• Resistance to flow (EN ISO 7390)	≤3 mm	
• Loss of volume (EN ISO 10563)	≤25 %	
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF	
• Adhesion/cohesion at variable temperatures (EN ISO 9047)	NF	
• Microorganisms, intensity of growth (EN ISO 846)	2	
<b>Durability:</b>	Pass	
Conditioning method B / Tested on concrete M2, without primer		

NPD = No performance determined.

NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo  
Product Manager  
13619 Tallinn, Estonia



1292

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

22

DoP Nr: KR-043100

**EN 15651-1:2012**

Sealant for facade for interior and exterior applications, suitable for use in cold climates

Type: F-EXT-INT-CC

**EN 15651-3:2012**

Sealants for joints for non-structural use in sanitary areas

Type: S

Conditioning: method B

Substrate: concrete M2, without primer

<b>Reaction to fire</b>	Class F
<b>Release of chemicals dangerous to the environment and health</b>	NPD/see product safety data sheet
<b>Water tightness and air tightness, as:</b>	
• Resistance to flow (EN ISO 7390)	≤3 mm
• Loss of volume (EN ISO 10563)	≤25 %
• Tensile properties at maintained extension at -30°C (EN ISO 8340)	NF
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF
• Adhesion/cohesion at variable temperatures (EN ISO 9047)	NF
• Microorganisms, intensity of growth (EN ISO 846)	2
<b>Durability:</b>	Pass