SilAcryl Elastic 610 White

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: SilAcryl Elastic 610 White

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Consumer use): Sealant Relevant uses (Professional users): Sealant

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

> Wolf Group OÜ Suur-Paala 10 13619 Tallinn - Estonia

Phone: +372 605 9300 - Fax: +372 605 9315

sds@wolf-group.com www.wolf-group.com

1.4 **Emergency telephone number:** 999; 111; 844 892 0111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

The product is not classified as hazardous according to GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Hazard statements:

Not relevant

Precautionary statements:

Not relevant

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2Hisothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture composed of additives and acrylic polymers

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification Chemical name/Classification			
CAS: EC: REACH:	166412-78-8 431-890-2 01-0000017810-74- XXXX	Di-isononyl-cyclohexane-1,2-dicarboxylate Skin Irrit. 2: H315 - Warning	5 - <10 %	
CAS: EC: REACH:	107-21-1 203-473-3 01-2119456816-28- XXXX	Ethanediol Acute Tox. 4: H302; STOT RE 2: H373 - Warning (1)	0,1 - <1 %	
CAS: EC: REACH:	2634-33-5 220-120-9 01-2120761540-60- XXXX	1,2-benzisothiazol-3(2H)-one Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	0,01 - <0,1 %	

- CONTINUED ON NEXT PAGE -

SilAcryl Elastic 610 White

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification	Chemical name/Classification	Concentration
CAS: EC:	55965-84-9 911-418-6	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<0,01 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification		M-factor	
1,2-benzisothiazol-3(2H)-one	Acute	10	
CAS: 2634-33-5		1	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Acute	100	
CAS: 55965-84-9	Chronic	100	

Identification	Specific concentration limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5	% (w/w) >=0,05: Skin Sens. 1 - H317
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxic	Genus	
1,2-benzisothiazol-3(2H)-one	LD50 oral	490 mg/kg	Rat
CAS: 2634-33-5 EC: 220-120-9	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87.12 mg/kg	Rabbit
EC: 911-418-6	LC50 inhalation vapour	1.433 mg/L *	

^{*} Equivalent ATE value of the substance applicable to the exposure route of the product. For the ATE value associated with the exposure route of the substance, see section 11.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 2/11

PENOSIL

Safety data sheet According to UK REACH (S.I. 2019/758)

SilAcryl Elastic 610 White

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

Special hazards arising from the substance or mixture: 5.2

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 **Environmental precautions:**

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

Reference to other sections:

See sections 8 and 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 3/11

SilAcryl Elastic 610 White

SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
Ethanediol (1)	WEL (8h)	20 ppm	52 mg/m³
CAS: 107-21-1	WEL (15 min)	40 ppm	104 mg/m³

⁽¹⁾ Skin

DNEL (Workers):

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Di-isononyl-cyclohexane-1,2-dicarboxylate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 166412-78-8	Dermal	Not relevant	Not relevant	42 mg/kg	Not relevant
EC: 431-890-2	Inhalation	Not relevant	Not relevant	235 mg/m³	Not relevant
Ethanediol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 107-21-1	Dermal	Not relevant	Not relevant	106 mg/kg	Not relevant
EC: 203-473-3	Inhalation	Not relevant	Not relevant	Not relevant	35 mg/m³
1,2-benzisothiazol-3(2H)-one	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 2634-33-5	Dermal	Not relevant	Not relevant	0.966 mg/kg	Not relevant
EC: 220-120-9	Inhalation	Not relevant	Not relevant	6.81 mg/m³	Not relevant
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 55965-84-9	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 911-418-6	Inhalation	Not relevant	0.04 mg/m³	Not relevant	0.02 mg/m³

DNEL (General population):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Di-isononyl-cyclohexane-1,2-dicarboxylate	Oral	Not relevant	Not relevant	2 mg/kg	Not relevant
CAS: 166412-78-8	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
EC: 431-890-2	Inhalation	Not relevant	Not relevant	70 mg/m³	Not relevant
Ethanediol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 107-21-1	Dermal	Not relevant	Not relevant	53 mg/kg	Not relevant
EC: 203-473-3	Inhalation	Not relevant	Not relevant	Not relevant	7 mg/m³

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 4/11

SilAcryl Elastic 610 White

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short e	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 2634-33-5	Dermal	Not relevant	Not relevant	0.345 mg/kg	Not relevant
EC: 220-120-9	Inhalation	Not relevant	Not relevant	1.2 mg/m³	Not relevant
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Oral	0.11 mg/kg	Not relevant	0.09 mg/kg	Not relevant
CAS: 55965-84-9	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 911-418-6	Inhalation	Not relevant	0.04 mg/m³	Not relevant	0.02 mg/m³

PNEC:

Identification				
Di-isononyl-cyclohexane-1,2-dicarboxylate	STP	Not relevant	Fresh water	Not relevant
CAS: 166412-78-8	Soil	44.7 mg/kg	Marine water	Not relevant
EC: 431-890-2	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
Ethanediol	STP	199.5 mg/L	Fresh water	10 mg/L
CAS: 107-21-1	Soil	1.53 mg/kg	Marine water	1 mg/L
EC: 203-473-3	Intermittent	10 mg/L	Sediment (Fresh water)	37 mg/kg
	Oral	Not relevant	Sediment (Marine water)	3.7 mg/kg
1,2-benzisothiazol-3(2H)-one	STP	1.03 mg/L	Fresh water	0.00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0.000403 mg/L
EC: 220-120-9	Intermittent	0.0011 mg/L	Sediment (Fresh water)	0.0499 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.00499 mg/kg
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	STP	0.23 mg/L	Fresh water	0.00339 mg/L
CAS: 55965-84-9	Soil	0.01 mg/kg	Marine water	0.00339 mg/L
EC: 911-418-6	Intermittent	0.00339 mg/L	Sediment (Fresh water)	0.027 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.027 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Not relevant

D.- Eye and face protection

Not relevant

E.- Body protection

Not relevant

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

It is not necessary to take additional emergency measures.

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 5/11





SilAcryl Elastic 610 White

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. (Supply): 1.27 % weight

V.O.C. density at 20 °C: 17.97 kg/m³ (17.97 g/L)

SEC	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES						
9.1	Information on basic physical and chemical proper	ties:					
	For complete information see the product datasheet.						
	Appearance:						
	Physical state at 20 °C:	Liquid					
	Appearance:	Not relevant *					
	Colour:	White					
	Odour:	Not relevant *					
	Odour threshold:	Not relevant *					
	Volatility:						
	Boiling point at atmospheric pressure:	339 °C					
	Vapour pressure at 20 °C:	957 Pa					
	Vapour pressure at 50 °C:	4879.52 Pa (4.88 kPa)					
	Evaporation rate at 20 °C:	Not relevant *					
	Product description:						
	Density at 20 °C:	1420 kg/m³					
	Relative density at 20 °C:	1.442					
	Dynamic viscosity at 20 °C:	Not relevant *					
	Kinematic viscosity at 20 °C:	Not relevant *					
	Kinematic viscosity at 40 °C:	Not relevant *					
	Concentration:	Not relevant *					
	pH:	Not relevant *					
	Vapour density at 20 °C:	Not relevant *					
	Partition coefficient n-octanol/water 20 °C:	Not relevant *					
	Solubility in water at 20 °C:	Not relevant *					
	Solubility properties:	Not relevant *					
	Decomposition temperature:	Not relevant *					
	Melting point/freezing point:	Not relevant *					
	Flammability:						
	Flash Point:	Non Flammable (>60 °C)					
	Flammability (solid, gas):	Not relevant *					
	Autoignition temperature:	343 °C					
	Lower flammability limit:	Not relevant *					
	Upper flammability limit:	Not relevant *					
	Particle characteristics:						
	Median equivalent diameter:	Not relevant *					
9.2	Other information:						
	Information with regard to physical hazard classes:	:					
	Explosive properties:	Not relevant *					
	Oxidising properties:	Not relevant *					
	Corrosive to metals:	Not relevant *					
	*Not relevant due to the nature of the product, not providing information	ation property of its hazards.					

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced **Page 6/11**

SilAcryl Elastic 610 White

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Heat of combustion: Not relevant *

Aerosols-total percentage (by mass) of flammable Not relevant 3

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant *

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 7/11

SilAcryl Elastic 610 White

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Distillates (petroleum), hydrotreated light (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Di-isononyl-cyclohexane-1,2-dicarboxylate	LD50 oral	>2000 mg/kg	
CAS: 166412-78-8	LD50 dermal	>2000 mg/kg	
EC: 431-890-2	LC50 inhalation vapour	>20 mg/L	
Ethanediol	LD50 oral	500 mg/kg	
CAS: 107-21-1	LD50 dermal	>3500 mg/kg	Rabbit
EC: 203-473-3	LC50 inhalation vapour	>20 mg/L	
1,2-benzisothiazol-3(2H)-one	LD50 oral	490 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	>2000 mg/kg	
EC: 220-120-9	LC50 inhalation dust	>5 mg/L	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87.12 mg/kg	Rabbit
EC: 911-418-6	LC50 inhalation mist	0.33 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix):

	-	
	Ingredient(s) of unknown toxicity	
Oral	>2000 mg/kg (Calculation method)	0 %
Dermal	>2000 mg/kg (Calculation method)	0 %
LC50 inhalation vapour	>20 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced

Safety data sheet

According to UK REACH (S.I. 2019/758)

SilAcryl Elastic 610 White

SECTION 12: ECOLOGICAL INFORMATION (continued)

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Ethanediol	LC50	53000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-21-1	EC50	51000 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	24000 mg/L (168 h)	Selenastrum capricornutum	Algae
1,2-benzisothiazol-3(2H)-one	LC50	2.18 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2634-33-5	EC50	2.9 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0.11 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	0.28 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 55965-84-9	EC50	0.007 mg/L (48 h)	Acartia tonsa	Crustacean
	EC50	0.0199 mg/L (72 h)	Skeletonema costatum	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	NOEC	>0.001 - 0.01 mg/L		Fish
CAS: 55965-84-9	NOEC	>0.001 - 0.01 mg/L		Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradat	pility
Ethanediol	BOD5	0.47 g O2/g	Concentration	100 mg/L
CAS: 107-21-1	COD	1.29 g O2/g	Period	14 days
EC: 203-473-3	BOD5/COD	0.36	% Biodegradable	90 %
1,2-benzisothiazol-3(2H)-one	BOD5	Not relevant	Concentration	1 mg/L
CAS: 2634-33-5	COD	Not relevant	Period	63 days
EC: 220-120-9	BOD5/COD	Not relevant	% Biodegradable	85 %
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	BOD5	Not relevant	Concentration	0.3 mg/L
CAS: 55965-84-9	COD	Not relevant	Period	29 days
EC: 911-418-6	BOD5/COD	Not relevant	% Biodegradable	38.8 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
Ethanediol	BCF	10	
CAS: 107-21-1	Pow Log	-1.36	
EC: 203-473-3	Potential	Low	
1,2-benzisothiazol-3(2H)-one	BCF	7	
CAS: 2634-33-5	Pow Log	0.7	
EC: 220-120-9	Potential	Low	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	BCF	54	
CAS: 55965-84-9	Pow Log	0.75	
EC: 911-418-6	Potential	Moderate	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volat	ility
Ethanediol	Koc	0	Henry	1.327E-1 Pa·m³/mol
CAS: 107-21-1	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	4.989E-2 N/m (25 °C)	Moist soil	Not relevant

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced

SilAcryl Elastic 610 White

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volat	ility
1,2-benzisothiazol-3(2H)-one	Koc	9.33	Henry	Not relevant
CAS: 2634-33-5	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Koc	7.7	Henry	5E-3 Pa·m³/mol
CAS: 55965-84-9	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class
ſ	08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	Non-hazardous

Type of waste:

Not relevant

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Not relevant

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

- CONTINUED ON NEXT PAGE -

Printing: 05/08/2025 Date of compilation: 24/03/2022 Revised: 10/12/2024 Version: 3 (Replaced Page 10/11

PENOSIL



Safety data sheet

According to UK REACH (S.I. 2019/758)

SilAcryl Elastic 610 White

SECTION 15: REGULATORY INFORMATION (continued)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

Classification procedure:

Not relevant

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the seccurity requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.