

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-052100**

Version 24.01.2024



1 / 3

---

**1. Unique identification code of the product-type:**

Penosil Acrylic Sealant 636

---

**2. Intended use/uses:**

Sealant for facade for interior and exterior applications (F-EXT-INT)  
Sealants for joints for non-structural use in sanitary areas (S)

---

**3. Manufacturer:**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**4. Authorized representative:**

Not relevant

---

**5. System or systems of assessment and verification of constancy of performance (AVCP):**

System 3 for the type testing  
System 3 for the reaction to fire

---

**6. Harmonised standard:**

EN 15651-1:2012  
EN 15651-3:2012

**Notified body/ies:**

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-052100**

Version 24.01.2024



2 / 3

**7.1 Declared performance:**

EN 15651-1:2012; Type F-EXT-INT, class 12,5P

| Essential characteristics:   | Performance:                      | Harmonised technical specification |
|--|-----------------------------------|------------------------------------|
| <b>Reaction to fire</b>  | Class E                           | EN 15651-1:2012                    |
| <b>Release of chemicals dangerous to the environment and health</b>              | NPD/see product safety data sheet |                                    |
| <b>Water tightness and air tightness, as:</b>                                    |                                   |                                    |
| • Resistance to flow (EN ISO 7390)   | ≤3 mm                             |                                    |
| • Loss of volume (EN ISO 10563)  | ≤25 %                             |                                    |
| • Tensile properties, elongation at break at +23°C (EN ISO 8339)                 | ≥25%                              |                                    |
| • Tensile properties at maintained extension (EN ISO 8340)                       | NF                                |                                    |
| • Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590) | NF                                |                                    |
| • Adhesion/cohesion at variable temperatures (EN ISO 9047)                       | NF                                |                                    |
| <b>Durability:</b>   | Pass                              |                                    |
| Conditioning method A / Tested on concrete M2, without primer                    |                                   |                                    |

NPD = No performance determined.

NF= No Failure.

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-052100**

Version 24.01.2024



3 / 3

**7.2 Declared performance:**

EN 15651-3:2012; Type S, klass XS2

| Essential characteristics:   | Performance:                      | Harmonised technical specification |
|--|-----------------------------------|------------------------------------|
| <b>Reaction to fire</b>  | Class E                           | EN 15651-3:2012                    |
| <b>Release of chemicals dangerous to the environment and health</b>              | NPD/see product safety data sheet |                                    |
| <b>Water tightness and air tightness, as:</b>                                    |                                   |                                    |
| • Resistance to flow (EN ISO 7390)   | ≤3 mm                             |                                    |
| • Loss of volume (EN ISO 10563)  | ≤25 %                             |                                    |
| • Tensile properties at maintained extension (EN ISO 8340)                       | NF                                |                                    |
| • Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590) | NF                                |                                    |
| • Adhesion/cohesion at variable temperatures (EN ISO 9047)                       | NF                                |                                    |
| • Microorganisms, intensity of growth (EN ISO 846)                               | 2                                 |                                    |
| <b>Durability:</b>   | Pass                              |                                    |
| Conditioning method A / Tested on concrete M2, without primer                    |                                   |                                    |

NPD = No performance determined.

NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Tõnis Erissaar  
 Product Manager  
 13619 Tallinn, Estonia  
 24.01.2024



1292

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

22

DoP Nr: KR-052100

**EN 15651-1:2012**

Sealant for facade for interior and exterior applications

Type: F-EXT-INT

**EN 15651-3:2012**

Sealants for joints for non-structural use in sanitary areas

Type: S

Conditioning: method A

Substrate: concrete M2, without primer

|  |                                   |
|--|-----------------------------------|
| <b>Reaction to fire</b>  | Class E                           |
| <b>Release of chemicals dangerous to the environment and health</b>              | NPD/see product safety data sheet |
| <b>Water tightness and air tightness, as:</b>                                    |                                   |
| • Resistance to flow (EN ISO 7390)   | ≤3 mm                             |
| • Loss of volume (EN ISO 10563)  | ≤25 %                             |
| • Tensile properties, elongation at break at +23°C (EN ISO 8339)                 | ≥25%                              |
| • Tensile properties at maintained extension (EN ISO 8340)                       | NF                                |
| • Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590) | NF                                |
| • Adhesion/cohesion at variable temperatures (EN ISO 9047)                       | NF                                |
| • Microorganisms, intensity of growth (EN ISO 846)                               | 2                                 |
| <b>Durability:</b>   | Pass                              |