

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-078100

Version 15.01.2025



1 / 2

1. Unique identification code of the product-type:
PENOSIL FireStop Intumescent Graphite Acrylic 682

2. Intended use/uses:
Sealant for facade for interior application only (F-INT)

3. Manufacturer:
Wolf Group OÜ
Suur-Paala 10
13619 Tallinn
ESTONIA

4. Authorized representative:
Not relevant

5. System or systems of assessment and verification of constancy of performance (AVCP):
System 4 for the type testing
System 3 for the reaction to fire

6. Harmonised standard:
EN 15651-1:2012
Notified body/ies:
0370 - LGAI TECHNOLOGICAL CENTER, S. A./Applus

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-078100

Version 15.01.2025



2 / 2

7.1 Declared performance:
EN 15651-1:2012; Type F-INT

Essential characteristics:	Performance:	Harmonised technical specification
Reaction to fire	Class C	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD/see product safety data sheet	
Water tightness and air tightness, as:		
• Resistance to flow (EN ISO 7390)	≤5 mm	
• Loss of volume (EN ISO 10563)	≤45 %	
• Tensile properties, elongation at break at +23°C (EN ISO 8339)	≥25%	
Durability:	Pass	
Conditioning method A / Tested on concrete M2, without primer		

NPD = No performance determined.
NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kaia Koitmäe
Product Manager
13619 Tallinn, Estonia
15.01.2025



0370

Wolf Group OÜ
Suur-Paala 10
13619 Tallinn
ESTONIA
24
DoP Nr: KR-078100

EN 15651-1:2012

Sealant for facade for interior application only
Type: F-INT
Conditioning: method A
Substrate: concrete M2, without primer

Reaction to fire	Class C
Release of chemicals dangerous to the environment and health	NPD/see product safety data sheet
Water tightness and air tightness, as:	
• Resistance to flow (EN ISO 7390)	≤5 mm
• Loss of volume (EN ISO 10563)	≤45 %
• Tensile properties, elongation at break at +23°C (EN ISO 8339)	≥25%
Durability:	Pass