

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-662100**

Version 04.09.2026



1 / 2

---

**1. Unique identification code of the product-type:**

PENOSIL SpeedFix Seal&Bond 700

---

**2. Intended use/uses:**

Sealant for facade for interior and exterior applications, suitable for use in cold climates (F-EXT-INT-CC)

---

**3. Manufacturer:**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**4. Authorized representative:**

Not relevant

---

**5. System or systems of assessment and verification of constancy of performance (AVCP):**

System 3 for the type testing  
System 3 for the reaction to fire

---

**6. Harmonised standard:**

EN 15651-1:2012

**Notified body/ies:**

1292 - FUNDACION TECNALIA RESEARCH & INNOVATION  
0074 - GINGER CEBTP

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-662100**

Version 04.09.2026



2 / 2

## 7.1 Declared performance:

EN 15651-1:2012; Type F-EXT-INT-CC, class 25HM

| Essential characteristics:                                                        | Performance:                      | Harmonised technical specification |
|-----------------------------------------------------------------------------------|-----------------------------------|------------------------------------|
| Reaction to fire                                                                  | Class E                           | EN 15651-1:2012                    |
| Release of chemicals dangerous to the environment and health                      | NPD/see product safety data sheet |                                    |
| Water tightness and air tightness, as:                                            |                                   |                                    |
| • Resistance to flow (EN ISO 7390)                                                | ≤3 mm                             |                                    |
| • Loss of volume (EN ISO 10563)                                                   | ≤10 %                             |                                    |
| • Tensile properties at maintained extension at -30°C (EN ISO 8340)               | NF                                |                                    |
| • Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)  | NF                                |                                    |
| Durability:                                                                       | Pass                              |                                    |
| Conditioning method A / Tested on concrete M2, anodized aluminium, without primer |                                   |                                    |

NPD = No performance determined.

NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo  
Product Manager  
13619 Tallinn, Estonia  
04.09.2026



1292 / 0074

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

26

DoP Nr: KR-662100

**EN 15651-1:2012**

Sealant for facade for interior and exterior applications, suitable for use in cold climates

Type: F-EXT-INT-CC

Conditioning: method A

Substrate: concrete M2, anodized aluminium, without primer

|                                                                                  |                                   |
|----------------------------------------------------------------------------------|-----------------------------------|
| <b>Reaction to fire</b>                                                          | Class E                           |
| <b>Release of chemicals dangerous to the environment and health</b>              | NPD/see product safety data sheet |
| <b>Water tightness and air tightness, as:</b>                                    |                                   |
| • Resistance to flow (EN ISO 7390)                                               | ≤3 mm                             |
| • Loss of volume (EN ISO 10563)                                                  | ≤10 %                             |
| • Tensile properties at maintained extension at -30°C (EN ISO 8340)              | NF                                |
| • Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590) | NF                                |
| <b>Durability:</b>                                                               | Pass                              |