PENOSIL

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-042100

Version 1 / April 2022

I. Unique identification code of the product-type: PENOSIL Universal Seal&Fix Hybrid 711c

2. Intended use/uses:

Sealant for joints on the external and internal side of facade elements (intended for use in cold climates: -30 °C) (F-EXT-INT-CC: class 20HM)

3. Manufacturer:

OÜ KRIMELTE Suur-Paala 10 13619 Tallinn ESTONIA

4. Authorised representative:

Not relevant

5. System or systems of assessment and verification of constancy of performance (AVCP):

System 3 for the type testing. System 4 for the reaction to fire.

6. Harmonised standard:

EN 15651-1:2012 EN 15651-2:2012 **Notified body/ies:** 1292 - FUNDACION TECNALIA RESEARCH & INNOVATION Page 1 Of 2

(F

PENOSIL

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-042100

Version 1 / April 2022

7. Declared performance:

Essential characteristics:	Performance:	<u>Harmonised</u> <u>technical</u> specification
Reaction to fire (EN 15501-1:2007+ A1:2010)	Class F	EN 15651-1:2012 EN 15651-2: 2012
Release of chemicals dangerous to the environment and health	See product SDS	
Water tightness and air tightness, as:		
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 10 %	
 Tensile properties (i.e. at maintained extension) at -30 °C (modif. EN ISO 8340) 	NF	
 Tensile properties at maintained extension after water immersion (EN ISO 10590) 	NF	
Durability:	Pass	
Conditioning method A / Tested on anodized aluminium, without primer.		

NPD = No performance determined NF= No Failure

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo Product Manager 13619 Tallinn, Estonia 14/04/2022

Page 2 Of 2

CE