

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-567100**

Version 24.07.2025



1 / 2

---

**1. Unique identification code of the product-type:**

PENOSIL SpeedFix Crystal 799

---

**2. Intended use/uses:**

Sealant for facade for interior application only (F-INT)

---

**3. Manufacturer:**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

---

**4. Authorized representative:**

Not relevant

---

**5. System or systems of assessment and verification of constancy of performance (AVCP):**

System 4 for the type testing  
System 4 for the reaction to fire

---

**6. Harmonised standard:**

EN 15651-1:2012  
**Notified body/ies:**  
Not relevant. - 0

---

# Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

**DoP Nr: KR-567100**

Version 24.07.2025



2 / 2

## 7.1 Declared performance:

EN 15651-1:2012; Type F-INT

Essential characteristics:	Performance:	Harmonised technical specification
Reaction to fire	Class F	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD/see product safety data sheet	
Water tightness and air tightness, as:		
• Resistance to flow (EN ISO 7390)	≤5 mm	
• Loss of volume (EN ISO 10563)	≤45 %	
• Tensile properties, elongation at break at +23°C (EN ISO 8339)	≥25%	
Durability:	Pass	
Conditioning method A / Tested on concrete M2, without primer		

NPD = No performance determined.

NF= No Failure.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo  
Product Manager  
13619 Tallinn, Estonia  
24.07.2025



**Not relevant.**

Wolf Group OÜ  
Suur-Paala 10  
13619 Tallinn  
ESTONIA

**25**

DoP Nr: KR-567100

**EN 15651-1:2012**

Sealant for facade for interior application only

Type: F-INT

Conditioning: method A

Substrate: concrete M2, without primer

<b>Reaction to fire</b>	Class F
<b>Release of chemicals dangerous to the environment and health</b>	NPD/see product safety data sheet
<b>Water tightness and air tightness, as:</b>	
• Resistance to flow (EN ISO 7390)	≤5 mm
• Loss of volume (EN ISO 10563)	≤45 %
• Tensile properties, elongation at break at +23°C (EN ISO 8339)	≥25%
<b>Durability:</b>	Pass