

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-019100



Version 1 / May 2023

Page 1 of 2

1. Unique identification code of the product-type:

PENOSIL PU-Sealant HM 868

2. Intended use/uses:

Sealant for facade for interior and exterior applications, suitable for use in cold climates (F-EXT-INT-CC: class 25HM)

Sealant for non-structural movement joints in floors for interior and exterior use, suitable for use in cold climates (PW-EXT-INT-CC: class 25HM)

3. Manufacturer:

Wolf Group OÜ
Suur-Paala 10
13619 Tallinn
ESTONIA

4. Authorised representative:

Not relevant

5. System or systems of assessment and verification of constancy of performance (AVCP):

System 3 for the type testing.

System 3 for the reaction to fire.

6. Harmonised standard:

EN 15651-1:2012

EN 15651-4:2012

Notified body/ies:

0074 - GINGER CEBTP

Declaration of Performance

(according to Annex III of the Regulation (EU) No 305/2011)

DoP Nr: KR-019100



Version 1 / May 2023

7. Declared performance:

<u>Essential characteristics:</u>	<u>Performance:</u>	<u>Harmonised technical specification</u>
Reaction to fire (EN 15501-1:2007+ A1:2010)	Class E	EN 15651-1: 2012 EN 15651-4: 2012
Release of chemicals dangerous to the environment and health	See product SDS	
Water tightness and air tightness, as:		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 10 %	
• Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	NF	
• Tensile properties at maintained extension at -30°C (EN ISO 8340)	NF	
• Tear resistance (modif. EN ISO 8340)	NF	
• Adhesion/cohesion properties after water immersion (modif. EN ISO 10590 with 28 days water immersion)	NF	
• Adhesion/cohesion properties after salt water immersion (modif. EN ISO 10590 with 28 days water immersion)	NF	
Durability:	Pass	
Conditioning method A / Tested on mortar M1 substrates, without primer.		

NF= No Failure

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuldar Kongo
Product Manager
13619 Tallinn, Estonia
04.05.2023