



2-3

## Cleaning

Uncured sealant can be cleaned with solvents like white spirit, acetone or with special cleaning wipes.  
Cured sealant can be removed mechanically.

## Technical data

Properties	Value	Unit
Basis	Bitumen	
Skin forming time	10...12	min
Curing rate	3...4	mm/24h
Application temperature	+5 ... +40	°C
Service temperature	-35 ... +110	°C
Shelf life	18	months
Shore A hardness (ISO 868)	20...24	

The values specified were obtained at +23 °C and 50% relative humidity, unless otherwise specified. These values may vary depending on environmental factors such as temperature, moisture and type of substrates.

## Colour

Black.

## Package

300 ml cartridge, 12 pcs in a box.

## Storage conditions and shelf life

Guaranteed shelf life 18 months from the manufacturing date when stored in a closed original package in a dry place and protected from direct sunlight at temperatures between +5 °C and +30 °C.

## Limitations

- No adhesion to PE, PP, PTFE (Teflon®).
- We don't recommend this product to be used for natural stone sealing
- Due to the wide variety of possible substrates, we recommend a preliminary compatibility and adherence test. If necessary, prime surfaces to improve adhesion.
- Due to the wide variety of influences during and after application, the customer must always test the product first.
- Please observe the expiration date!

## Safety regulations

Ensure sufficient ventilation during application and wear necessary personal protective equipment.  
More specific safety information is available on the safety data sheet (SDS).

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice.  
This TDS replaces and supersedes all previous data sheets on the same product.