www.penosil.com

Wolf Group Head Office Suur-Paala 10 13619 Tallinn

tel +372 605 9300 fax +372 605 9315 info@penosil.com

TECHNICAL DATA SHEET

PENOSIL Sealant Remover 990

High-performance cleaner designed for the thorough removal of silicone, grease, oil, wax, dirt, tar, MS polymers, and adhesive residues from various surfaces.

Main Benefits

- Swift and comprehensive removal
- Suitable for ceramic, non-porous metallic and polymer surfaces
- Sprayable
- Instant effect

Fields of application

- Removal of silicone, grease, and other contaminants from surfaces.
- Cleaning of tools and equipment after use
- Pre-treatment for surfaces to ensure better adhesion of subsequent coatings or treatments.

Application instructions

Application conditions

Air and can temperature during use: $+5^{\circ}$ C to $+30^{\circ}$ C.

Surface preparation

Ensure surface is dry and free of large deposits. Remove hardened substances mechanically using a sharp tool.

Application method

Apply the product with a spray. Let the product react for 30 seconds. In case of sealants and adhesives, while the sealant remover is reacting with the product, scrape off the thin layer of silicone or adhesive using a small tool that doesn't damage the surface (sealant scraper). Wipe off and let it evaporate. Repeat process if necessary.

Cleaning

Wipe off excess product with clean cloth or tissue and let evaporate. Rinse the area with water if necessary.

Colour

Colourless.

Package

270 ml aerosol can, content 200 ml, 12 pcs in a box.

Storage conditions and shelf life

Guaranteed shelf life 24 months from the manufacturing date when stored in closed original package in a dry place and protected from direct sunlight and heat sources at temperatures between +5 °C and +30 °C.



www.penosil.com

Wolf Group Head Office Suur-Paala 10 13619 Tallinn Estonia

tel +372 605 9300 fax +372 605 9315 info@penosil.com

Limitations

- Test small area first to ensure compatibility with surfaces!
- May dissolve paint and other coatings from surfaces. Beware of coloured surfaces. The product will stain painted areas.
- Observe the expiration date.

Safety regulations

Pressurized canister. Use only in well-ventilated areas. Do not smoke during application! Use protective gear when necessary (gloves). Keep out of reach from children. See label and safety data sheet (SDS) for more information.

Note: The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials and substrates as well as the various application possibilities that are beyond our control, the manufacturer is not liable for the results achieved. In any case, it is recommended to test the product suitability at the place of application. Manufacturer reserves the right to modify products without prior notice.

This TDS replaces and supersedes all previous data sheets on the same product.